

Polycom VSX 8400/8800 Specifications

ITU H.323 and H.320 compliant
Cisco AVVID Certified

Bandwidth

- Maximum Data Rate IP and Serial/V.35: Up to 2 Mbps
- Maximum Data Rate ISDN: Up to 2 Mbps

Video Standards & Protocols

- H.261, Annex D
- H.263+ Annexes: F, I, J, L, N, T
- H.263++ Annexes: W
- H.264
- 1U 60-fps full screen – Pro-Motion

Frame Rates (Point-to-Point)

- Intelligently selects frame rate for best performance video
- 30 fps at 56 kbps up to 2 Mbps
- 60 fields per second up to 2 Mbps

Video Inputs: 4 Connectors

- 1 x S-Video; Professional Y/C BNCs (main video camera)
 - 1 x DB15; PowerCam and PowerCam Plus power, PTZ control, IR, mic input
- 1 x S-Video; 4-pin mini DIN (second camera with PTZ control)
- 1 x S-Video; 4-pin mini DIN (VCR or DVD player)
- 1 x VGA (Content input from laptop)

Serial Data Port: 2 Connectors

- 2 x DB9
- Control port for custom integration with remote devices such as Crestron and AMX control systems
- Integration with Polycom Vortex® Installed Voice Products
- Communication port for transmission of serial data (i.e. medical devices) over ISDN calls
- Auxiliary camera control

Video Outputs: 4 Connectors

- 1 x S-Video; Professional Y/C BNCs (main display)
- 1 x S-Video; 4-pin mini DIN (second display)
- 1 x S-Video; 4-pin mini DIN (VCR or DVD player)
- 1 x VGA (Content display)

Video Formats

- NTSC/PAL
- Graphics: XGA, SVGA, VGA

People Video Resolution

- Pro-Motion interlaced video (60/50 fields full-screen video for NTSC/PAL)
- 4SIF (704 x 480)
- 4CIF (704 x 576)
- SIF (352 x 240)
- CIF (352 x 288)
- Choice of 4:3 or 16:9 display aspect ratios
- Display People on VGA Second Monitor

Content Video Resolution

- XGA (1024 x 768), SVGA (800 x 600), VGA (640 x 480) for Content on 2nd VGA Displays (when used with primary NTSC/PAL display)
- People video support for 4CIF and SIF on 2nd VGA display
- Single monitor graphics display (800 x 600)
- Up to 4CIF for Content on NTSC/PAL displays

Audio Standards & Protocols

- Polycom StereoSurround ready
- 14 kHz bandwidth with Siren™ 14 on IP, ISDN, and IP/ISDN mixed calls
- 7 kHz bandwidth with G.722, G.722.1
- 3.4 kHz bandwidth with G.711, G.728, G.729A

Audio Features

- Seamless integration with Polycom Vortex Installed Voice Products
- Audio add-in using SoundStation VTX 1000 conference phone
- Audio add-in over ISDN
- Audio add-in over POTS
- Full-duplex digital audio
- Instant Adaptation Echo Cancellation
- Automatic Gain Control (AGC) – Voice activated
- Automatic Noise Suppression (ANS)
- Audio Mixer (Mic, VCR, line-in)
- Built-in tonal speaker test
- Real-time audio level meter for local and far-end microphones
- Microphone and VCR input audio mixing
- Ability to talk over VCR audio
- Ability to turn off Echo Cancellation when external audio equipment is used

Audio Inputs: 6 Connectors

- 1 x Conference link
 - Supports up to (3) microphones
 - Supports SoundStation VTX 1000 conference phone
- 2 x RCA/Phono, line level input for VCR, DVD player or audio mixer

- 2 x Phoenix connectors; balanced line level or direct microphone inputs with 24 V Phantom power
- 1 x RJ-11 for analog speaker telephone

Audio Outputs: 6 Connectors

- 2 x Phoenix connectors; balanced line level output
- 2 x RCA/Phono, Line Level output for VCR record
- 2 x RCA/Phono, Line Level output for speakers

Polycom Digital Tabletop Microphone

- 360° voice pick up, 4.8 dB less reverberant than omni microphone
- Three cardioid elements per microphone
- Flotation feet reduce transmission of tabletop noise
- Integrated mute button
- Can be mounted to ceiling or walls

Other ITU-Supported Standards

- H.221 communications
- H.224/H.281 far-end camera control
- Annex Q standard for FECC in H.323 calls
- H.225, H.245, H.331
- H.239 People+Content
- H.231 in multipoint calls
- H.243 MCU password
- H.233, H.234, H.235V3 encryption standards
- Bonding, Mode 1

Network Interfaces Supported

- IP (LAN, DSL, cable modem)
- Single 10/100 Ethernet port (10 bps/100Mbps/Auto)
- Optional ISDN QBRI (Basic Rate Interface) Module
- Optional ISDN PRI (Primary Rate Interface) Module T1/E1
- Optional Serial Module (V.35/RS-530/RS-449 with RS-366 dialing)

Network Features

- Integration with Cisco Systems' CallManager Version 4.0
- Automatic IP/ISDN calling
- Down speeding over IP and ISDN
- Audio & Video Error Concealment over IP and ISDN, mixed calls
- IP address conflict warning
- Fast Connect IP for quick video connections
- Maximum call length digital timer
- Auto SPID detection and line number configuration
- MGC™ Click&View™ for individual screen layouts
- Polycom OneDial™ intelligent call management attempts call on preferred network (IP or ISDN) and automatically rolls over to secondary network if needed
- Polycom PathNavigator support for easy call placement and network cost optimisation
- TCP/IP, UDP/IP, RTP, DNS, WINS, DHCP, ARP, HTTP, FTP, Telnet
- SIP Support (Session Initiation Protocol)
- Chair control through API command or Integrated Web Interface
- Software Upgradeable Inverse Multiplexer (IMUX)

Conference on Demand

- Initiates unscheduled MGC calls from the endpoint
- Utilises Polycom Office (PathNavigator and MGC)
- Auto selects either the internal or external bridge
- Dials all participants simultaneously

Security

- COMSEC tested by Titan Systems, Information Security Systems Division, and independently validated to operate with approved government encryption technologies
- KG-194/KIV-7 encryptor support with on screen and address book dialing
- Enhanced integration for independently certified, classified encryption devices
- Account validation number entry
- Secure password authentication
- Unique factory default passwords
- Administrator password
- Dial-in meeting password
- Encrypted password for VSX Web access
- Ability to disable mixed protocol multipoint calls
- Auto-Answer (On/Off)
- Allow access to user settings (On/Off)

Embedded Encryption

- Advanced Encryption Standard (AES)
- FIPS validated by National Institute of Standards & Technology (NIST) certified agency
- 128-bit key length
- AES software encryption on ISDN, IP and Serial/V.35 up to 2 Mbps
- Standards-based H.235V3 (IP)
- Standards-based H.233/H.234 (ISDN/Serial)
- Automatic key generation and exchange
- Supported in People+Content
- Supported in Point-to-Point IP, ISDN and mixed network calls

User Interface

- User-friendly graphical interface
- Customisable home screen and color themes
- Kiosk mode with scrolling marquee
- User-selectable camera icons and ring tones
- Up to (99) user defined camera presets
- Speed Dial List on home page
- Persistent Preview (Far-site PIP) on all screens
- Picture-In-Picture (PIP) (On/Off, Moveable)
- Dual-Monitor Emulation
- Numerical menu navigation (Similar to mobile phone)
- Date, Time Server accessibility
- Calendar and Conference scheduling
- Alert Signal on home page
- Do Not Disturb (On/Off)
- VSX Web for remote monitoring

Directory Services

- 4,000+ number global directory
- 1,000+ number local directory
- Limitless multipoint entries
- Live address book with Polycom Global Directory Services automatically and quickly updates directory with address changes or new endpoints
- Live address book with Polycom Global Directory Services automatically and quickly removes endpoints from directory if they are turned off
- Polycom Global Directory Services integrates with Active Directory/LDAP
- Directory Server backup in the event Polycom Global Directory is not accessible
- Automatic ISDN localisation of calls

System Management

- SNMP for enterprise management
- Diagnostics and software upgrades via PC, LAN
- Integrated VSX Web management tool
- Web Director: Remote administrator video monitoring and control from VSX Web (enabled/disabled from endpoint for security)
- Out-of-box setup from VSX Web
- Place a call from VSX Web
- Language independence between set-top interface and VSX Web
- System configuration from VSX Web
- Recent Calls Log – Records last 99 incoming and outgoing calls
- Call Detail Record (CDR) – Reports all incoming and outbound calls along with call statistics
- CDR Feature On/Off
- Downloadable CDR data for processing requires no external management system
- Account number validation at call initiation integrated with Polycom Global Management System™ for billing purposes
- Administrator-configurable dialing speeds
- Complete support for The Polycom Office™ including:
 - Polycom Global Management System
 - Polycom OneDial
 - Polycom PathNavigator
 - Polycom Conference Suite
 - Polycom MGC
 - Polycom SoundStation VTX 1000
 - Polycom Vortex

Quality of Service and Experience – iPriority™

- Video Error Concealment
- Audio Error Concealment
- Universal Plug and Play (UPnP)
- IP Precedence (ToS)
 - Configurable video/audio/FECC service value
- DiffServ (DSCP) (COS)
- Dynamic Bandwidth Allocation
- Proactive Network Monitoring
- Packet and jitter control
- Network Address Translation (NAT) support
- Automatic NAT discovery
- Asymmetric speed control
- Alternate Gatekeeper support
- TCP/UDP fixed-port firewall support
- Lip synchronisation
- Echo cancellation
- Echo suppression
- Auto gatekeeper discovery
- Automatic gateway dialing profiles
- Specify outbound call routing for gateway/ISDN

Collaboration Solutions

- People+Content™ IP
 - Show content from laptop/PC over IP network connection
 - No resolution adjustment required on presenter's laptop/PC
 - Supports CIF, SIF, 4CIF, 4SIF, VGA, SVGA, XGA display resolutions
 - Zoom control
 - Supports Windows 2000 and Windows XP
 - PC Utility available for unlimited download (required for each presenter's laptop/PC)

- Closed captioning support
- Web Streaming in and out of a call, RTP based, suitable with QuickTime® players

Language Support (12 languages)

- Chinese (Simplified), Chinese (Traditional), English, French, German, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Spanish
 - Documentation translations in all languages
 - User interface translations in all languages
 - Keypad audio dialing confirmation in all languages
 - VSX Web translations in all languages
 - Remote controls labeled in all languages

Electrical

- Auto sensing power supply
- Operating voltage/power 85-264 VAC, 47-63 Hz/ 72 Watts

Environmental Specifications

- Operating Temperature: 0-40°C
- Operating Humidity: 15-80%
- Non-Operating Temperature: -40-70°C
- Non-Operating Humidity (Non-condensing): 10-90%

Physical Characteristics

- Video Base Unit (W/H/D): 438.15 mm/43.83 mm/245.85 mm (17.25"/1.73"/9.68")
- Video Base Unit Weight: 3.8 kg/8.4 lbs

Warranty

- One-year return to factory parts and labor
- One-year software updates and upgrades

VSX 8800 Includes

- PowerCam™ Plus Camera
 - Silent, motorised pan-tilt-zoom camera with imbedded microphones enables pointing to presets
- Tilt Range: +/- 25° (Up/Down)
- Pan Range: +/- 100° (Left/Right)
- Horizontal field of view: 65°
- Total Field of View: 265°
- Horizontal resolution: 460 (PAL)/470 (NTSC) TV lines
- Zoom range: 10x
- Auto focus/white balance/brightness/iris
- Standards-based, far-end camera control (FECC)

Polycom Digital Tabletop Microphones (2)

- 360° voice pick up, 4.8 dB less reverberant than omni microphone
- Three cardioid elements per microphone
- Flotation feet reduce transmission of tabletop noise
- Integrated mute button
- Can be mounted to ceiling or walls
- People+Content Support
- People+Content IP
- ImageShare™ II
- Direct VGA-in connectivity

Internal Multipoint Features

- Mixed protocol dialing connects a total of four endpoints (IP/ISDN/Serial) through the internal MCU
- Dial-in/Dial-out Calling (IP/ISDN/Serial)
- Password protection for incoming calls
- Supports IP telephones
- Automatic IP/ISDN down speeding
- Supports People+Content from any endpoint (Not just the host site)
- Voice Activated Switching – view current speaker
- Continuous Presence – see all locations
- Automatic Presentation – switch between presenter and continuous presence mode
- MP key installation while in a call
- Audio add-in over ISDN
- Cascading for up to 10 conference participants (mix of IP/ISDN/Serial Video and ISDN Audio)

Stereo Speaker Kit

- Includes subwoofer, (2) high-fidelity speakers and speaker stands
- Subwoofer: 150 watts output power; bass response to 35 Hz
- Speakers: frequency range 100 Hz to 22 kHz

VSX 8400 Includes

- PowerCam Camera
 - Ultra-quiet, ultra-fast action pan-tilt-zoom (PTZ)
- Tilt Range: +/- 25° (Up/Down)
- Pan Range: +/- 100° (Left/Right)
- Horizontal field of view: 65°
- Total Field of View: 265°
- Horizontal resolution: 460 (PAL)/470 (NTSC) TV lines
- Zoom range: 10x
- Auto focus/white balance/brightness/iris
- Standards-based, far-end camera control (FECC)

Polycom Digital Tabletop Microphones (2)

- See details above
- People+Content Support
- See details above

©2004 Polycom, Inc. All rights reserved.

Polycom, the Polycom logo and Vortex are registered trademarks and VSX, Polycom PathNavigator, Global Management System, Siren, Pro-Motion, MGC, Click&View, Polycom OneDial, People+Content, The Polycom Office, iPriority, PowerCam, Polycom StereoSurround and SoundStation VTX 1000 are trademarks of Polycom, Inc. All other trademarks are the property of their respective owners. Information in this document is subject to change without notice.



Polycom EMEA:

270 Bath Road, Slough, Berkshire SL1 4DX, (T) +44 (0)1753 723000, (F) +44 (0)1753 723010

Polycom Headquarters:

4750 Willow Road, Pleasanton, CA 94588 (T) 1.800.POLYCOM (765.9266) for North America only.
For North America, Latin America and Caribbean (T) +1.925.924.6000, (F) +1.925.924.6100

Polycom Asia Pacific:

Polycom Hong Kong Ltd., Rm 1101 MassMutual Tower, 38 Gloucester Road, Wanchai, Hong Kong, (T) +852.2861.3113, (F) +852.2866.8028

Part No. 3726-17108-002 Rev. 02/05